



Since 1991

JANDI'S INDUSTRIAL CO., LTD.

尚宏機械工業有限公司

A-B-C 3 LAYER CO-EXTRUSION FILM INFLATION MACHINE A-B-C 三層複合吹膜機



JANDI'S[®]

The Quality You Want 品質與承諾

A-B-C 3 LAYER CO-EXTRUSION FILM INFLATION MACHINE (A-B-C三層複合吹膜機)

	MODEL 型號	GF-E3C-45-55-45	GF-E3C-45-65-45	GF-E3C-50-65-50	GF-E3C-55-65-55	GF-E3C-65-85-65
FEATURE 性能	MATERIAL TO BE USED 用料	LDPE / LLDPE / mLLDPE / HDPE / EVA / PP				
	MAX. FILM WIDTH 最大寬度	1000mm	1200mm	1500mm	1800mm	2400mm
	FILM THICKNESS 膠膜厚度	0.02mm ~ 0.20mm	0.02mm ~ 0.20mm	0.02mm ~ 0.20mm	0.02mm ~ 0.20mm	0.03mm ~ 0.20mm
	LAYER RATIO 厚度比例	1:1:1 TO 1:3:1	1:1:1 TO 1:3:1	1:1:1 TO 1:3:1	1:1:1 TO 1:3:1	1:1:1 TO 1:3:1
	MAX. EXTRUSION CAPACITY 最大押出量	120kg/hr for 1:1:1	120kg/hr for 1:1:1	180kg/hr for 1:1:1	240kg/hr for 1:1:1	420kg/hr for 1:1:1
		160kg/hr for 1:2:1	160kg/hr for 1:2:1	240kg/hr for 1:2:1	280kg/hr for 1:2:1	400kg/hr for 1:2:1
REAL PRODUCTION OUTPUT 實際生產量	REAL PRODUCTION OUTPUT DEPENDS ON THE MATERIAL, FILM SIZE, OPERATION CONDITIONS, SKILL & EXPERIENCE 實際生產量依照使用原料, 產品規格, 操作條件, 生產經驗和技術而有所差別					
EXTRUDER 押出機 (THREE SETS) 共三套	SCREW DIAMETER 螺桿直徑	45mm x 2 55mm x 1	45mm x 2 65mm x 1	50mm x 2 65mm x 1	55mm x 2 65mm x 2	65mm x 2 5mm x 1
	SCREW L/D RATIO 螺桿長徑比	30:1	30:1	30:1	30:1	30:1
	DRIVING MOTOR 傳動馬達	20HP X 2 40HP X 1	20HP X 2 60HP X 1	30HP X 2 60HP X 1	40HP X 2 75HP X 1	60HP X 2 100HP X 1
	BLOWN FILM DIES 模頭	ψ200mm	ψ250mm	ψ300mm	ψ375mm	
CONTROL PANEL 控制箱	TYPE 型式	INDEPENDENT TYPE SWITCH BOARD (BOX) 獨立式控制箱				
	TEMP. CONTROL 溫控	PID TEMPERATURE CONTROLLERS, COLD-START PROTECTION 微電腦溫度控制器, 冷車保護				
COOLING UNIT 冷卻設備	TYPE 類型	EXTERNAL AIR COOLING TYPE, BY DUALLIP AIR RING 雙層風環, 外部冷卻式				
TAKE-UP UNIT 引取機	FIXED TOWER, HEIGHT 固定式	7 M (米)	8 M (米)	10 M (米)	12 M (米)	14 M (米)
	OSCILLATING HAUL-OFF 上旋轉	HORIZONTAL TYPE, SITTING ON SLEWING RING BEARING, OSCILLATING IN NEARLY 360° 平行式, 工業級轉盤軸承				
	TAKE UP ROLLER 引取輪寬	1100mm	1300mm	1600mm	1900mm	1900mm
	TAKE UP MOTOR 引取馬達	1HP	1HP	2HP	3HP	5HP



	MODEL 型號	GF-E3C-45-55-45	GF-E3C-45-65-45	GF-E3C-50-65-50	GF-E3C-55-65-55	GF-E3C-65-85-65
	TAKE-UP SPEED 引取速度	MAX. 60M/min or TO BE SPECIFIED BY BUYER 最快 60 米/分鐘, 或由客戶指定				
	BUBBLE GUIDE 安定環	CAGE TYPE, BY MANUAL or MOTOR DRIVE 環抱式, 手動或馬達驅動升降/張和				
	STEADY PLATE 安定板	MANUAL /MOTOR DRIVEN TYPE , MADE OF ALUMINUM ROLLERS 鋁輪組,手動或馬達驅動張和				
	GUSSET BOARD 折角板	OPTIONS, PLEASE SPECIFY MAX. GUSSET DEPTH REQUIRED 選配, 請註明最大折角深度				450mm DEPTH 深度
	GUIDE UNIT 引導裝置	BY TORQUE MOTOR or AC MOTOR + INVERTER 轉距馬達或 AC 馬達+變頻控制				
	AIR BLOWER 冷卻設備	7.5HP	10HP	15HP	15HP	20HP
WINDING UNIT 捲取裝置	TYPE 類型	SINGLE/TWO STATION SURFACE WINDER or BOBBIN WINDER or SCGC (SURFACE /CONTACT/GAP/CENTRAL) 4-IN-1 WINDER 全自動PLC或HMI, 單邊或雙邊磨擦式捲取機, 或 中心捲軸式捲取機, 或 SCGC (磨擦式/接觸式/間隙式/中心式)四合一捲取機				
	BOBBIN CHANGE 換捲裝置	PNEUMATIC SYSTEM or MANUAL TYPE 氣壓式 或 手動式				
	FILM CUTTING 切斷裝置	氣壓式 或 手動式				
	EFFECTIVE WIDTH 有效寬度	1100mm	1200mm	1500mm	1800mm	1800mm
	WOUND-UP DIAMETER 最大捲徑	Max. 800mm or TO BE SPECIFIED BY BUYER 直徑 800mm, 或由客戶指定				
	WINDING MOTOR 捲取馬達	1HP	1HP	2HP	2HP	5HP
OPTIONS 選購設備	GRAVIMETRIC DOSING UNIT, AUTO HOPPER LOADER, SATURN AIRRING, PRESSURE & MELTING TEMP GAUGE, THICKNESS MEASUREMENT, EXTRUSION CONTROL WIDTH CONTROLLER,INTERNAL BUBBLE COOLING(IBC), VERTICAL TYPE OSCILLATING TAKE UP UNIT, CORONA TREATER, HEAT-SLITTING UNIT, 6" AIR SHAFTS, EDGE POSITION CONTROL (EPC), CENTER POSITION CONTROL(CPC), AUTO. TENSION CONTROL, HYDRAULIC UNLOADING UNIT, AIR CHILLING SYSTEMetc. 比例進料, 吸料機, 加拿大風環, 壓力計和熔膠測溫, 厚度偵測, 押出控制, 寬度控制, 內外冷卻, 垂直式上旋轉, 表面處理機, 熱分條裝置, 6" 氣壓軸, 自動對邊裝置, 自動對中裝置, 自動張力控制, 油壓卸料裝置, 冷風設備等等					
REMARKS 備註	<ul style="list-style-type: none"> Final specifications of the co-extrusion machine depend on the film application, material to be used, accepted thickness tolerance, and your special requirements. 客製化的機器規格, 依照您的產品 / 產量 / 原料 / 厚度比例 / 容許誤差和其他需求等等, 來設定最適合您的機器的規格					



GF-L3C-65T
Film 1800mm, 400kg/hr



GF-E3C-45-65-45 3 LAYER CO-EXTRUSION
Film 1200mm, 200kg/hr

- WITH CE CERTIFICATE
- VERTICAL TYPE OSCILLATION UNIT
- FILM GAUGING UNIT / U.K.
- EDGE POSITION CONTROL
- DWA + U-TYPE WINDER
- 2-COLOR FLEXO IN-LINE PRINTING



J.I. MANUFACTURER & EXPORTER SINCE 1991
JANDI'S INDUSTRIAL CO., LTD.
尚宏機械工業有限公司

Horizontal type oscillation haul off
平行式上旋轉引取裝置



3 Layer (A-B-C) Co-extrusion
三層(A-B-C)複合吹袋



®
TM

Since 1991

JANDI'S INDUSTRIAL CO., LTD.
DESIGNER & MANUFACTURER/ IMPORTER & EXPORTER

No. 46-1 Chung-Shang Road, Min-Hsiung Industrial District,
Chia-Yi Hsien 621, Taiwan
Tel: +886-5-2200506 (5lines) Fax: +886-5-220 1955
E-mail: jandis@ms7.hinet.net jandi@ms19.hinet.net



www.jandis.com.tw



尚宏機械工業有限公司

621嘉義縣民雄鄉民雄工業區中山路46-1號
統一編號:23975144
電話: (05)220-0506(5線)
傳真: (05)220-1955
鄧白氏編碼(D-U-N-S® No.): 65-740-8712
台灣區機器工業同業公會 會員編號70141號
MEMBER OF TAIWAN ASSOCIATION OF MACHINERY
INDUSTRY TAMI NO. 70141



www.inflationmachine.com